


Media: air
 Inlet Pressure: 10 Bar max
 Pressure range: 0.5 – 10 Bar
 Media temp: -10°C to +60°C
 Ambient temp: -10°C to +60°C
 Mounting: any position



Miniature FRL

1/8 1/4
 Aluminium
 Manual, Semi & Auto Drain
 0.5 – 10 Bar
TYPE FRL7,6,5 +200



PRESSURE

Ø Port BSP	Max Flow Air (L/Min) @ 6Bar (ANR)	Kg	Pressure (Bar)		Combination	Part Number
			Min	Max		
1/8(01)	1850	0.81	0.5	10	F+R+L	FRL700A + port
	1650,1850	0.56	0.5	10	FR+L	FRL600A + port
1/4(02)	1840,1940	0.37	0.5	10	FR	FR500A
	1900	0.245	0.5	10	Filter	F200A
	2449	0.165	0.5	10	Lubricator	L200A

OPTIONS

5 µm PE Filter element , Semi-Automatic drain below 0.5 Bar, Pressure Gauge, Plug, Mounting Bracket & screws (FRL700,600,FR500)
 40 µm PE Filter element (C)
 5 µm (S) or 40 µm(T) Sintered Bronze element
 Manual Drain (H)
 Full auto drain (D)
 Acid alkali resistant bowls (A)
 Bowl Guard (K) (FRL700+600 x2, FR500,F200A, L200A x1)
 Mounting bracket (option for F200A & L200A)
 NPT Thread

CONSTRUCTION

Diaphragm Regulator, Filter (35cc), Lubricator (50cc)
 Body & Bowls: Polycarbonate
 Recommended Oil ISO VG32

FEATURES

Ultra-compact high accuracy high flow diaphragm pressure regulation long life
 Lubricator oil refill under during full working pressure

12 Bar Proof Pressure Tested
 Secure Oil mist delivery and adjustment

OVERALL DIMENSIONS

