



No	Part Name	Material
1	Gauge	-----
2	Cover	Stainless Steel #CF8M
3	U-Ring	NBR / Viton
4	Shaft	Stainless Steel #316
5	Sealing Spacer	NBR / Viton
6	Shaft	Stainless Steel #316
7	Mail Body	Stainless Steel #CF8M
8	Diaphragm Cover	Stainless Steel #CF8M
9	Diaphragm	EPDM / Viton
10	Fixed Bolt	Stainless Steel #304
11	Spring	Spring Steel
12	Spring Cover	Stainless Steel #CF8M
13	Spring Washer	Brass
14	Adjusting Bolt	Stainless Steel #304

Item No	PN16	H	L	D	CV*
RFLF-15-S	1/2"	110	150	105	2.4
RFLF-20-S	3/4"	125	150	105	9
RFLF-25-S	1"	125	150	105	11
RFLF-40-S	1 1/2"	155	190	145	21
RFLF-50-S	2"	155	190	145	25

Unit : mm

\* Applied Fluid : Water, Air.

\* Pressure Adjusting Range : 0.2 kgf/cm<sup>2</sup> ~ 1.5 kgf/cm<sup>2</sup>  
( Special order is needed for particular fluid. )

\* Applied Temperature : -15°C ~ 80°C

\* Pressure gauge indicates the inlet pressure.