

### Features

1. Direct acting.
2. Quick response.
3. Timer for setting on/off time as optional accessory.
4. Good performance on resistance of counter flow.
5. Coil nut is available, please refer to page 5-3, 5-4.



### How to order

<b>SPUY220</b>	<b>-</b>	<b>04</b>	<b>N</b>	<b>E</b>	<b>S1</b>	<b>L</b>
<b>Angle type</b>		<b>Port size</b>	<b>Thread</b>	<b>Diaphragm</b>	<b>Solenoid</b>	<b>Led</b>
<b>Direct Acting</b>		<b>04 : 1/2"</b>	<b>Blank : G</b> <b>N : NPT</b> <b>R : Rc</b>	<b>Blank : VITON</b> <b>E : EPDM</b> <b>H : HNBR</b>	<b>S1 : 110VAC</b> <b>S2 : 220VAC</b> <b>S9 : 24VDC</b>	<b>Blank : W/O LED</b> <b>L : W/I LED</b>

\*Please contact our sales for normally open type.

### Specifications

Model	SPUY220-04
Port size	1/2"
Fluid	Standard: Compressed air Option: Hot water, Ammonia, Vacuum
Orifice	9.5mm
Effective area	27.6mm <sup>2</sup>
Acting	Direct acting
Seal	Standard: VITON, Option: EPDM
Operating pressure range	0 ~ 8 kgf/cm <sup>2</sup>
Proof pressure	15 kgf/cm <sup>2</sup>
Body material	SUS316
Fluid temperature	-10°C ~ 90°C
Ambient temperature	-10°C ~ 60°C
Installation	Horizontal
Duty cycle	100% ED
Coil type	DIN
Protection class	IP65 (DIN 40 050)
Insulation class	F
Voltage tolerance	± 10%
Standard voltage	220VAC, 110VAC, 24VDC
Power consumption	AC110V: 25VA, AC220V: 27VA, 24VDC: 18.5W
Net weight	440g

### Dimensions

