


Media: air – water – light oil
 Pressure range: 1 to 300 Bar max
 Media temperature: 100°C max
 Ambient temperature: -10° to +50°C
 Media viscosity: 40 centistokes max
 Mounting: vertical position, coil up
 Weight (including coil): 550 g
 Opening or Closing time: 100mSec Max



2/2 Stainless

1/8 – 1/4

NORMALLY CLOSED

2 WAY SERVO ASSISTED

1 – 300 Bar

TYPE 206252-259



PRESSURE

Ø Port BSP	Ø Orifice (mm)	Flow Kv Ltr/ min	Pressure (Bar) ΔP			Seals	Max Media Temp °C	Part Number
			Min	Max air	Max water - oil			
1/8 or 1/4	6	5.0	1	50		NBR EPDM FKM	60 100 100	20625210 + port + voltage 20625230 + port + voltage 20625220 + port + voltage
			1		50	NBR EPDM FKM	60 100 100	20625310 + port + voltage 20625330 + port + voltage 20625320 + port + voltage
			1	100		NBR EPDM FKM	60 100 100	20625410 + port + voltage 20625430 + port + voltage 20625420 + port + voltage
			1		100	NBR EPDM FKM	60 100 100	20625510 + port + voltage 20625530 + port + voltage 20625520 + port + voltage
			1	200		NBR EPDM FKM	60 100 100	20625610 + port + voltage 20625630 + port + voltage 20625620 + port + voltage
			1		200	NBR EPDM FKM	60 100 100	20625710 + port + voltage 20625730 + port + voltage 20625720 + port + voltage
			1	300		PTFE NBR PTFE EPDM PTFE FKM PTFE	60 100 100 180	20625881 + port + voltage 20625883 + port + voltage 20625882 + port + voltage 20625880 + port + voltage
			1		300	PTFE NBR PTFE EPDM PTFE FKM PTFE	60 100 100 180	20625981 + port + voltage 20625983 + port + voltage 20625982 + port + voltage 20625980 + port + voltage

OPTIONS

IP65 Coil & Connector PG9 – DIN 43650 A
 NPT thread
 PTFE seal
 Explosion proof enclosure: Protection II G/D EExdIICT6 ATEX

ELECTRICAL DATA

Voltage (-10% + 15%) Continuous duty 100%	Coil	Power Consumption		Insulation class	Enclosure	Electrical connections
		Inrush	Holding			
~ 24 - 48 - 110 - 230 (50 or 60 Hz)	10065	48 VA	24 VA	F 155°C	IP 65 with connector	DIN 43650A DIN 40050 VDE 0110
= 12 - 24 - 48 (DC)		14 – 20 Watts				

CONSTRUCTION

Body: AISI 316L
 Tube and internal parts: Stainless steel
 Seals and gaskets: NBR (Optional EPDM, FKM & PTFE)
 Moulded coil: Resin

REPAIR KIT

Coil	10065 + voltage
Complete plunger + O' rings + complete piston	KIT + valve part number

OVERALL DIMENSIONS

