

Size	Specs	Out dia	Inside dia	Thickness	Center	Hole size	Nos of hole	Size	Specs	Out dia	Inside dia	Thickness	Center	Hole size	Nos of hole
1/2"	10K	95	22.5	12	70	15	4	3"	10K	185	90	18	150	19	8
	16K	95	22.5	14	70	15	4		16K	200	90	22	160	23	8
	150P	89	22.3	11.2	60.3	15	4		150P	190	90.7	23.9	152.4	19	4
	300P	95	22.3	14.3	66.7	19	4		300P	210	90.7	28.6	168.3	22	8
	PN16	95	22.5	14	65	15	4		PN16	200	90	20	160	19	8
										7.5K	211	90	18	168	18
3/4"	10K	100	28	14	75	15	4	4"	10K	210	116	18	175	19	8
	16K	100	28	16	75	15	4		16K	225	116	24	185	23	8
	150P	98	27.7	12.7	69.8	15	4		150P	229	116.1	23.9	190.5	19	8
	300P	117	27.7	15.1	82.5	19	4		300P	254	116.1	31.8	200	22	8
	PN16	105	28	16	75	15	4		PN16	220	116	20	180	19	8
										7.5K	238	115.4	18	195	18
1"	10K	125	34.5	14	90	19	4	5"	10K	250	142	20	210	23	8
	16K	125	34.5	16	90	19	4		16K	270	142	26	225	25	8
	150P	108	34.5	14.3	79.4	15	4		150P	254	143.8	23.9	215.9	22	8
	300P	124	34.5	17.5	90	19	4		300P	279	143.8	35	234.9	22	8
	PN16	115	34.5	16	85	15	4		PN16	250	142	22	210	19	8
										7.5K	263	141.2	19	220	18
1 1/4"	10K	135	43.5	16	100	19	4	6"	10K	280	167	22	240	23	8
	16K	135	43.5	18	100	19	4		16K	305	167	28	260	25	12
	150P	117	43.2	15.9	88.9	15	4		150P	279	170.7	25.4	241.3	22	8
	300P	133	43.2	19.1	98.4	19	4		300P	318	170.7	36.6	269.9	22	12
	PN16	140	43.5	16	100	19	4		PN16	285	167	22	240	23	8
										7.5K	290	166.6	20	247	18
1 1/2"	10K	140	50	16	105	19	4	8"	10K	330	218	22	290	23	12
	16K	140	50	18	105	19	4		16K	350	218	30	305	25	12
	150P	127	49.5	17.5	98.4	15	4		150P	343	221.5	28.6	298.4	22	8
	300P	156	49.5	20.7	114.3	19	4		300P	381	221.5	41.3	330.2	25	12
	PN16	150	50	16	110	19	4		PN16	340	218	24	295	23	12
										7.5K	342	218	21	299	18
2"	10K	155	61.5	16	120	19	4	10"	10K	400	270	24	355	25	12
	16K	155	61.5	18	120	19	8		16K	430	270	34	380	27	12
	150P	152	62	19.1	120.6	19	4		150P	276.3	406	30.2	361.9	25	12
	300P	165	62	22.3	127	22	8		300P	444	276.3	47.7	387.3	29	16
	PN16	165	61.5	18	125	19	4		PN16	405	270	26	355	27	12
	7.5K	184	61.1	18	140	18	4		7.5K	410	269.5	22	360	21	8
2 1/2"	10K	175	77.5	18	140	19	4	12"	10K	445	320	24	400	25	16
	16K	175	77.5	20	140	19	8		16K	480	320	36	430	27	16
	150P	178	74.7	22.3	139.7	19	4		150P	483	327.1	31.8	431.8	25	12
	300P	190	74.7	25.4	149.2	22	8		300P	521	327.1	50.8	450.8	32	16
	PN16	185	77.5	18	145	19	4		PN16	460	320	28	412	27	12
	7.5K	193	77.1	18	155	18	4		7.5K	464	321	23	414	21	10

instruction manual:

Japanese specifications = JIS 7.5K 10K 16K

European specifications = PN16

U.S. specifications =150P(LB) 300P(LB)