


Media: air – water – light oil  
 Pressure range: 2 to 200 bar max  
 Media temperature: 150° C max  
 Ambient temperature: -10° to +60° C  
 Media viscosity: 40 centistokes max  
 Mounting: vertical position, coil up  
 Weight (including coil): 5000 g  
 Opening or Closing Time: 200mSec Max



# 2/2 Stainless

## 3/8 - 3/4

### NORMALLY CLOSED

### 2 WAY SERVO ASSISTED

### 2 – 300 Bar


## TYPE 212256-259



#### PRESSURE

Ø Port	Ø Orifice (mm)	Flow Kv Ltr/Min	Pressure Rating (Bar) ΔP			Seals	Max Media Temp °C	Part Number
			Min	Max Fluid	Max Gas - air			
3/8 or 1/2 or 3/4	12	30	2		200	PTFE + FKM	150	212256 + seal + port + voltage
				200				212257 + seal + port + voltage
3/8 or 1/2 or 3/4	12	30	10		300	Voltalef + FKM	150	212258 + seal + port + voltage
				300				212259 + seal + port + voltage

#### OPTIONS

IP65 Coil & Connector PG9 – DIN 43650 A  
 NPT 3/8 + 1/2 thread  
 NPT 3/4 Thread  
 Explosion proof enclosure: Protection II G/D EExdIIC6 ATEX   
 90° Between Inlet and Outlet

Included

#### ELECTRICAL DATA

Voltage (-10% + 15%) Continuous duty 100%	Coil	Power Consumption		Insulation class	Enclosure	Electrical connections
		Inrush	Holding			
~ 24 - 48 - 110 - 230 (50 or 60 Hz)	31037	48 VA	24 VA	F 155°C	IP 65 with connector	3 spades DIN 43650A DIN 40050 VDE 0110
= 12 - 24 - 48 (DC)		13.7 Watt				

#### CONSTRUCTION

Body: AISI 316L Stainless steel  
 Tube and internal parts: Stainless steel  
 Seals and gaskets: NBR (Optional EPDM or FKM)  
 Moulded coil: Resin

#### REPAIR KIT

Coil	31037 + voltage
Complete plunger + O' rings + complete piston	KIT + valve part number

#### OVERALL DIMENSIONS

