

# DATASHEET

|                             |  |
|-----------------------------|--|
| Date                        | : 18/12/2020   |
| Ordering Code               | : 34-III-24V-DC-66-MS-H-01   |
| Item Code                   | : F802000134   |
| Type of Solenoid            | : Explosion Proof Enclosure Ex ia having integrated Terminals, Bottom Cable Entry M20X1.5mm, IP67  |
| Size of Coil                | : III  |
| Voltage                     | : 24V DC   |
| Enclosure Material          | : Aluminium cast powder coated   |
| Approval                    | : IEC Ex + ATEX  |
| Power of Coil               | : 2.30W  |
| Insulation Class            | : H  |
| Certificate nr.             | : IECEX BAS 12.0128X - Issue 1, Baseefa12ATEX0243X - Issue 1   |
| Marking                     | : EX ia IIC T5, Ga (-60 °C ≤ Ta ≤ 75 °C)<br>EX ia IIC T6, Ga (-60 °C ≤ Ta ≤ 60 °C)<br>Ex ia IIIC T200 125 °C IP67 Da (-60 °C ≤ Ta ≤ 75 °C) |
| Entity Parameter            | : Ui - 32V DC Ii - 230mA Pi - 2.3W Li - 0 Ci - 0   |
| Minimum Operating Parameter | : V / I / W - 10V / 20mA / 0.20W   |

Created By: Sumit Rawat    Print Date And Time: 18/12/2020 20:26

This is System Generated Report