




# 1/2 WAY N.C. Y TYPE PISTON SERIES

## SOLENOID VALVE

YS0605



- Y Type Forged Brass Body
- IP65 100% ED Coil
- PTB Approval EExmIIT4 Coil

### POWER CONSUMPTION

COIL	4	5	3E
AC(VA)	17.6/15.4	33/23	9.2
DC(W)	15	18.5	10

### TYPE YA: For Water, Air and Higher Temp. Fluids

PIPE G	CODE NO.	SEAL MAT'L	COIL	ORIFICE mm	Temp. (-5 ~ °C)						Working Press. bar					Cv	
					Coil 4			Coil 5/3E			Coil 4		Coil 5		Coil 3E		
					N	J	V	N	J	V	AC	DC	AC	DC	AC/DC		
3/8"	10	N. J. V.	4. 5.3E	12	95	120		95	145			0.3~16	0.3~10	0.3~20	0.3~12	0.3~5	1.9
1/2"	15																2.6

### TYPE YS: For Steam and High Temp. Fluids

PIPE G	CODE NO.	SEAL MAT'L	COIL	ORIFICE mm	Temp. (-5 ~ °C)				Working Press. bar					Cv
					Coil 4/3E		Coil 5		Coil 4		Coil 5		Coil 3E	
					AC	DC	AC	DC	AC	DC	AC/DC			
3/8"	10	T*	4. 5.3E	12	158		185		0.3~5	0.3~2	0.3~10	0.3~7	0.3~5	1.9
1/2"	15													2.6


\* Teflon Seal will have 400cc/min. down gas leakage. Teflon Seal 400cc/min.

### TYPE INDICATION

TYPE	CODE	SEAL MAT'L	BODY MAT'L	COIL	PLUG	VOLTAGE
YA	10	N: NBR	C: Brass	4	□: DIN	G: 1/2 NPTF
YS	15	J: EPDM		5	D: LED	
		V: VITON		E		
		T: TEFLON				

### DIMENSIONS mm

TYPE	YA/YS
CODE	10   15
L	60.0
L	95.0
H	123.0
W	30/36
N.W. (kg)	0.55



Connexion  
Developments Ltd



Solenoid Valves (UK) Ltd.



ISO 9001