






Media: air
 Pressure range: 0 to 8 Bar
 External pilot: 1.5 to 7 Bar
 Media temperature: +80°C max
 Ambient temp: -10°C to +80°C max
 Mounting: any position
 Weight : 180, 375, 595g






3/2 Pneumatic Valve

1/8, 1/4, 3/8 & 1/2 BSP Width 26/30/34mm
 3/2 N/Closed + N/Open
 0 – 8 Bar
TYPE SK320

**3/2 Way Normally Closed Spring Return
 SK320S Series**

Ø Port BSP	Ø Orifice (mm ²)	Pressure Rating (Bar) ΔP		Max Working	Part Number	Width (mm)	
		Min	Max				
1/8	14	0	8	10	SK32001S	26	
1/4	18	0	8	10	SK32002S	26	
3/8	35	0	8	10	SK32003S	30	
1/2	70	0	8	10	SK32004S	34	

**3/2 Way Normally Open Spring Return
 SK320S Series**

Ø Port BSP	Ø Orifice (mm ²)	Pressure Rating (Bar) ΔP		Max Working	Part Number	Width (mm)	
		Min	Max				
1/8	14	0	8	10	SK320N01S	26	
1/4	18	0	8	10	SK320N02S	26	
3/8	35	0	8	10	SK320N03S	30	
1/2	70	0	8	10	SK320N04S	34	

OPTIONS


NPT Thread

CONSTRUCTION


Body: Anodised Aluminium
 Tube and internal parts: Stainless steel
 Seals and gaskets: NBR

OVERALL DIMENSIONS

SK32001/2



SK32003



SK32004

