

WRAS Brass Ball Valve – ISO 5211

WRAS Certificate number 2309911
valid until September 2028



Screwed BSPP, ISO 5211 Connection for Direct Mount

Pressure: 40 Bar Max

Temperature: -20°C to +95°C



Material	
Body:	Brass CW 617N
Ball:	Brass 617N
Seats:	PTFE
Steam	Brass CW 614N
O Rings	Viton

Torque (NM)						
Port	1/2	3/4	1	1 1/4	1 1/2	2
NM	4.2	4.8	5.5	11.5	18	22

Flow (Kv)						
Port	1/2	3/4	1	1 1/4	1 1/2	2
Kv	16.3	29.5	43	89	230	265

Dimensions (mm)											
Port	Orifice	H	S	F	A	C	ISO	ØD	□	□B	Kg
1/2	15	31	59	17	7	36	F03	5.5	38	9	0.3
3/4	20	37	69	18	8	36	F03	5.5	38	9	0.4
1	25	41	83	22	8	36	F03	5.5	38	9	0.7
1 1/4	32	46.5	94	24	14.5	50	F05	6.5	50	14	1.1
1 1/2	40	58	102	24	14.5	50	F05	6.5	50	14	1.4
2	50	65.5	124	28	14.5	50	F05	6.5	50	14	2.2

