

Media: air
 Pressure range: 0 to 9 Bar max
 Media temp: -10°C +60°C max
 Ambient temperature: -10°C to +60°C
 Mounting: any position
 Air pilot start pressure: 3.5 - 4.5 Bar

3/2 Mechanical 1/8

Normally Open or Closed 3 WAY DIRECT ACTING 0 – 9 Bar TYPE MSV30132



PRESSURE

Ø Port	Ø Orifice (mm²)	Pressure Rating (Bar)			Operator		Part Number
		Min ΔP	Max ΔP	Max	Type	Picture	
1/8 (01)	5.5mm²	0	9	10	Toggle Lever		MSV30132-01V
		0	9	10	Roller		MSV30132-01R
		0	9	10	Push Button		MSV30132-01P
		0	9	10	One Way Roller		MSV30132-01D
		0	9	10	Ball Plunger		MSV30132-01B
		0	9	10	Air Pilot		MSV30132-01A
		0	9	10	Finger Button		MSV30132-01F

OPTIONS

NPT or Rc Thread (MSV30132-01N)

CONSTRUCTION

Body : Aluminium alloy
 Panel dimension 12mm
 Internal parts : Stainless steel
 Seals and gaskets : NBR
 MSV30132-01P patent number ZL200530157285.1
 MSV30132-01V patent number ZL200530157282.8

OVERALL DIMENSIONS

